

Wall hood
Flat'line 90cm

7600/15
Stainless steel

EAN 5414425076000

Engery label

Energy efficiency class (EEIhood)	A+
Annual energy consumption (kWh/year) (AEChood)	33,4
Fluid Dynamic Efficiency class (FDEhood)	A
Lighting efficiency class (LEhood)	A
Grease filtering efficiency class (GFEhood)	D

General information

Motor integrated	•
Without motor, use remote motor inside, outdoor wall motor of flat roof motor	-
Kind of light	led (4x2W)
Dimmable light	•
With sound absorber	•
Recirculation	optional (Monoblock)

Dimensions (mm) (more detailed info can be found on the website)

Dimensions (WxD)	898 x 554
Height cookerhood (Hmin - Hmax)(mm)	660 - 1050
Height with recirculation (Hmin-Hmax)(mm)	730 - 1120
Maximum height with extended chimney (mm)(optional)	1410
Maximum height with extended chimney recirculation (mm)(optional)	1480
Advice mounting height with electrical and ceramic hobs (Hmin-Hmax)(mm)	600 - 750
Advice mounting height with gas and induction hobs (Hmin-Hmax)(mm)	650 - 750
Diameter outlet (mm)	150

Functions

Operation	touch buttons
Number of speed	3 + power
Powerspeed automatically to lower speed (minutes)	6
Delayed self switching off (minutes)	10
InTouch function for induction hob	optional
Auto-Stop	•
Light indicator for grease filter cleaning	•
Light indicator for recirculation filter cleaning/ substitution	•

Airflow and noise level

Maximum flow (m3/h)	815
Airflow (m3/h)(according to EN 61591)	
- Speed 1	271
- Speed 2	466
- Speed 3	616
- Powerspeed / speed 4	710
Pressure (Pa) on the highest speed (according to EN 61591)	372
Noise Level (dB(A) re 1 pW/ dB(A) re 20µPa) (according to EN 60704-2-13)	
- Speed 1	35 / 24
- Speed 2	47 / 36
- Speed 3	55 / 44
- Powerspeed / speed 4	57 / 46

Technical specifications

Number of grease filters	1
Total power (W)	119
The power consumption in off-mode in Watt (P0)	-
The power consumption in stand-by-mode in Watt (Ps)	0,3
Position exhaust	top
Weight cookerhood / motorunit (kg)	30



Wall hood
Flat'line 90cm

7600/15
Stainless steel

Accessories

Remote motor for inside use	-
Remote motor for outside on the wall	-
Flat roof motor	-
Extended chimney	7600100
Recirculation kit	7600400
Splashback panel:	
- 500 mm high	-
- 690 mm high	150200
- 750 mm high	150275
Kit for remote control (InTouch)	990026
Extended cable for seperated motor (5m)	-
Kit 4 x LED colour (natural white) 4000 K	906307

7600/15
Stainless steel



Wall hood
Flat'line 90cm

7600/15
Stainless steel

