



ENERG  
енергия · ενεργεια




ASKO

CH040



45.3  
kWh/annum



65/2014

200175

## OPLYSNINGSSKEMA

Model	CH040
Annual Energy Consumption - AEC <sub>hood</sub>	45,3 kWh/a
Energi klasse	C
Fluid Dynamic Efficiency - FDE	12,2 %
Fluid Dynamic Efficiency class	E
Light Efficiency - LE <sub>hood</sub>	38,1 lux/W
Lighting Efficiency Class	A
Grease Filtering Efficiency - GFE <sub>hood</sub>	92,0 %
Grease Filtering Efficiency class	B
A-weighted Sound Power Emission at minimum speed	170 m³/h
Maximum Air Flow in normal use	340 m³/h
Air Flow at intensive/boost setting	-
A-weighted Sound Power Emission at minimum speed	49 dB(A) re 1pW
A-weighted Sound Power Emission at maximum speed	64 dB(A) re 1pW
A-weighted Sound Power Emission at intensive or boost speed	-
Power consumption off mode - P <sub>o</sub>	-
Power consumption in standby mode - P <sub>s</sub>	-
Time increase factor	1,6
Energy Efficiency Index - EEI	80,9
Measured air flow rate at best efficiency point - Q <sub>bep</sub>	198,0 m³/h
Measured air pressure at best efficiency point - P <sub>bep</sub>	140,0 Pa
Maximum air flow - Q <sub>max</sub>	340 m³/h
Measured electric power input at best efficiency point - W <sub>bep</sub>	63,0 W
Nominal power of the lighting system - W <sub>L</sub>	11,0 W
Average illumination of the lighting system on the	419,0 lux

