



[Download EU Data Sheet](#)

# D79MH52N1B

## CHIMNEY HOOD 90 CM WIDE

### Product Features

#### FEATURES

- For wall mounted installation
- 7 segment LED display
- 3 x LED lights
- softLight with dimmer function
- 3 metal grease filter cassettes
- Saturation indicator for grease filter
- metal grease filter
- Interval operation
- 3 power levels and 2 intensive settings (10 minutes)
- Automatic intensive revert (6mins)
- Additional noise insulation
- 700EE

#### DESIGN

- Stainless steel
- Stainless steel with glass canopy
- 90 cm wide Chimney hood
- Box slimline brand design
- Soft touch control
- Electronic controls
- Light Colour: warm white

#### PERFORMANCE/TECHNICAL INFORMATION

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Twin channel high performance fan motor
- In recirculation operation chimless use possible
- Easy mounting system
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 460 m³/h
- Intensive 730 m³/h
- Power rating: 139 W
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 55 dB (A) re 1pW

Noise max. Normal Level: 55 dB\*  
Light Intensity: 897 lux  
Colour Temperature: 3500 K  
Electrical cable length 1.3 m  
Diameter pipe Ø 150 mm (Ø 120 mm enclosed)  
Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm  
Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm  
Dimensions recirculating with CleanAir module (HxWxD):  
689 x 900 x 500 mm - mounting with outer chimney  
809-1139 x 900 x 500 mm - mounting with telescopic chimney  
Energy Efficiency Class: A+\*  
Blower Efficiency Class: A\*  
Lighting Efficiency Class: A\*  
Grease Filtering Efficiency Class: C\*  
Average Energy Consumption: 32.5 kWh/year\*

#### OPTIONAL ACCESSORIES

- Recirculating kit Z5102X1, Z5102X5, Z5170X1, Z5276X0, Z5906N1,  
Z5916N1