



[Download EU Data Sheet](#)

D79MT62N1B

CHIMNEY HOOD 90 CM WIDE

Product Features

FEATURES

-

- For wall mounted installation
- 7 segment LED display
- 3 x LED lights
- softLight with dimmer function
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- metal grease filter
- Interval operation
- 3 power levels and 2 intensive settings (10 minutes)
- Automatic intensive revert (6mins)
- Additional noise insulation
- Efficient BLDC-technology

DESIGN

-

- Stainless steel
- Stainless steel with glass canopy
- 90 cm wide Chimney hood
- Box slimline brand design
- Touch control
- Electronic controls
- Light Colour: warm white

PERFORMANCE/TECHNICAL INFORMATION

-

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Twin channel high performance fan motor
- In recirculation operation chimless use possible
- Easy mounting system
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 460 m³/h
 - Intensive 860 m³/h
- Power rating: 169 W
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal

setting: extraction rate: 55 dB (A) re 1pW
Noise max. Normal Level: 55 dB*
Light Intensity: 897 lux
Colour Temperature: 3500 K
Electrical cable length 1.3 m
Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm
Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm
Dimensions recirculating with CleanAir module (HxWxD):
689 x 900 x 500 mm - mounting with outer chimney
809-1139 x 900 x 500 mm - mounting with telescopic chimney
Energy Efficiency Class: A+*
Blower Efficiency Class: A*
Lighting Efficiency Class: A*
Grease Filtering Efficiency Class: C*
Average Energy Consumption: 31.1 kWh/year*

OPTIONAL ACCESSORIES

- Recirculating kit Z5102X1, Z5102X5, Z5170X1, Z5276X0, Z5906N1,
Z5916N1