

DA 6690 D Puristic Edition 6000

Island cooker hood
with energy-efficient LED lighting and touch
controls for simple operation.

- Family design - to match Generation 6000 built-in appliances
- Unique convenience - Con@ctivity 2.0 ⓘ
- Powerful - 750m3/h on the booster setting
- Energy-efficient and quiet - powerful ECO motor ⓘ
- Pleasantly quiet - Miele acoustic package ⓘ



★★★★★ > Write a review



EU Datasheet





















Price: £ 3,199.00*

* Price incl. VAT




> Find a dealer



Product details - DA 6690 D Puristic Edition 6000

Construction type		^
Island cooker hood	•	
Design		^
Colour	Stainless steel	
RAL colours available as customisation on request	• ⓘ	
Customisation possible on request	• ⓘ	
Variable height available as customisation on request	•	
Variable width available as customisation on request	•	
Operating modes		^
Type of air guide	Convertible	
User convenience		^
Electronic controls	•	
Touch-on-glass controls	•	
Power levels (number without Booster level)	3	
Booster level	•	
Programmable Booster level switch-off	• ⓘ	
Run-on time 5 / 15 min.	• ⓘ	



Grease filter saturation indicator programmable	• 
Active charcoal filter saturation indicator programmable	• 
Silence package	• 
Cleaning convenience 	
Easy-to-clean canopy interior – CleanCover	• 
Efficiency and sustainability 	
Energy efficiency class	A+
Annual energy consumption in kWh/year	33.3
Fluid dynamic efficiency class	A
Lighting efficiency class	A 
Grease filtering efficiency class	A 
PowerManagement system	• 
ECO package	• 
Appliance networking 	
Miele@home	•
MobileControl	•
Automatic function Con@ctivity 2.0	• 
Filter system 	
Number of dishwasher safe stainless-steel grease filters (10-ply)	3
Lighting 	
LED	• 
Light intensity in Lx	640
Colour temperature in K	3,500
Fan 	
Dual-action fan	• 
ECO motor (DC motor)	• 
Air throughput with max. duct diameter in extraction mode (not for external version) 	
Air throughput in Level 1 (m³/h) according to EN 61591	220
Air throughput in Level 2 (m³/h) according to EN 61591	340
Air throughput in Level 3 (m³/h) according to EN 61591	500
Air throughput in Booster level (m³/h) according to EN 61591	750
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	36
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	45
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	55
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	65
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	21
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	30
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	40
Sound power in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	50
Air throughput in recirculation mode 	
Air throughput in Level 1 (m³/h) according to EN 61591	150

Air throughput in Level 2 (m³/h) according to EN 61591	260
Air throughput in Level 3 (m³/h) according to EN 61591	400
Air throughput in Booster level (m³/h) according to EN 61591	500
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	49
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	57
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	66
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	72
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	33
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	42
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	51
Sound power in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13	57

Safety	
Safety switch-off	• 
Single pane tempered glass	• 

Technical data	
Overall height for extraction mode and external mode cooker hoods in mm	705 - 1,005
Overall height for recirculation mode cooker hoods in mm	765 - 1,075
Canopy width in mm	898
Canopy height in mm	85
Canopy depth in mm	598
Minimum height above electric hobs in mm	450
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 	650
Net weight in kg	35.0
Hard-wired connection	•
Total rated load in kW	0.14
Voltage in V	230
Fuse rating in A	10
Number of phases	1

Installation notes	
Extraction ducting connection at top	•
Diameter of extraction ducting connection in mm	150
Telescopic chimney	• 

Standard accessories	
Non-return flap	• 
RF Con@tivity 2.0 communication stick for KM	XKS 3000 Z

Installation drawings

You may be replacing a household appliance or planning a new kitchen. Whatever the case, the relevant installation drawings can be found under Downloads.

To view an installation drawing, first click on the appropriate image to display the high-res version.

Then right click and save the image to your computer.

Please note that service and repair of our products should be carried out by a Miele authorised

Please note that service and repair of our products should be carried out by a Miele authorised service technician. Please contact us for further information.

Downloads

* Price incl. VAT

Subject to technical changes; no liability accepted for the accuracy of the information given

¹ Patent application WO 2009/127379 A2