

# Home Appliances

[Home Appliances](#) [Products](#) [Cooking & Baking](#) [Cooker hoods](#) [Island cooker hoods](#) [DIB091K50B](#)

**Serie | 8** Slimline box style  
90 cm wide island chimney hood  
DIB091K50B Brushed steel



[Buy now](#)




[Download EU Data Sheet](#)

**Customer Rating:**



[Be the first to review this product](#)

[Write a review](#)



**Stylish island chimney hoods perfectly complement island hob installations.**

- An impressive extraction rate of 850 m3/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.
- **Especially quiet:** high performance at just 48 dB.



### Technical specs

Key features

Electronic control via TouchControl

EcoSensor

Design

Designed for ceiling mounted installation

90 cm wide

Brushed steel

Inner frame

Features

TouchControl with lightline

3 power levels and 2 intensive settings

Automatic intensive revert (6mins)

Automatic after running: 10 min

Rim ventilation

Additional noise reduction insulation

4 x LED lights

Softlight dimmer function

Florescent mood lighting

Light Colour: warm white

3 removable metal grease filter cassettes

Filter cover stainless steel, Removable metal grease filters

Saturation indicator for metal and charcoal filter

Filter saturation indicator

Performance/technical information

Suitable for ducted or recirculating operation

Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 620 m³/h  
Intensive 850 m³/h

Extraction rate exhaust air according to EN 61591:  
max. normal use 620 m³/h, intensive 850 m³/h

Power rating: 272 W

Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 62 dB(A) re 1 pW (48 dB(A) re 20 µPa sound pressure)  
Intensive: 69 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)

Noise max. Normal Level: 62 dB\*

Average Energy Consumption: 46.7 kWh/year\*

Energy Efficiency Class: A\*

Blower Efficiency Class: A\*

Lighting Efficiency Class: A\*

Grease Filtering Efficiency Class: B\*

Dimensions exhaust air (HxWxD): 744-924 x 900 x 600 mm

Dimensions recirculating (HxWxD): 744-1044 x 900 x 600 mm

Dimensions recirculating with [CleanAir module](#) (HxWxD): 812-1044 x 900 x 600 mm

Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

Light Intensity: 888 lux

Colour Temperature: 3500 K

Efficient BLDC-technology

Optional accessories

For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed

\* In accordance with the EU-Regulation No 65/2014