

Home Appliances

[Home Appliances](#) [Products](#) [Cooking & Baking](#) [Cooker hoods](#) [Wall-mounted cooker hoods](#) DWB098J50B

Serie | 8 Slimline box style
90 cm wide Chimney extractor hood
DWB098J50B Brushed steel



[Buy now](#)




[Download EU Data Sheet](#)

Customer Rating:



[Be the first to review this product](#)

[Write a review](#)



Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your

kitchen planning.

- An impressive extraction rate of 860 m³/h ensures this hood will have your kitchen odour free in no time.
- LED lighting is highly energy efficient and provides attractive, white and even lighting for the hob area.
- Intensive speed setting with revert gives a quick intensive 6 min. burst to clear strong odours and then reverts back to the normal setting.
- **Especially quiet:** high performance at just 41 dB.



Technical specs

Key features

Electronic control via TouchControl

Design

Designed for wall mounted installation

90 cm wide

Brushed steel

Inner frame

Features

TouchControl with lightline

3 power levels and 2 intensive settings

Automatic intensive revert (6mins)

Automatic after running: 10 min

Additional noise reduction insulation

3 x LED lights

Softlight dimmer function

Florescent mood lighting

3 removable metal grease filter cassettes

Removable metal grease filters

Performance/technical information

Suitable for ducted or recirculating operation

Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 460 m³/h
Intensive 860 m³/h

Extraction rate exhaust air according to EN 61591:
max. normal use 460 m³/h, intensive 860 m³/h

Power rating: 169 W

Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 55 dB(A) re 1 pW (41 dB(A) re 20 µPa sound pressure)
Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)

Noise max. Normal Level: 55 dB*

Average Energy Consumption: 37.2 kWh/year*

Energy Efficiency Class: A+*

Blower Efficiency Class: A*

Lighting Efficiency Class: A*

Grease Filtering Efficiency Class: C*

Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm

Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm

Dimensions recirculating with [CleanAir module](#) (HxWxD): 809-1139 x 900 x 500 mm

Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

Light Intensity: 897 lux

Colour Temperature: 3500 K

Efficient BLDC-technology

Optional accessories

For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed

* In accordance with the EU-Regulation No 65/2014