



[Download EU Data Sheet](#)

I79MT64N1B

ISLAND CHIMNEY HOOD 90 CM WIDE

Product Features

FEATURES

-

- For ceiling mounted installation
- 7 segment LED display
- 4 x LED lights
- softLight with dimmer function
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- metal grease filter
- Interval operation
- 3 power levels and 2 intensive settings (10 minutes)
- Automatic intensive revert (6mins)
- Additional noise insulation
- Efficient BLDC-technology

DESIGN

-

- Stainless steel
- Stainless steel with glass canopy
- 90 cm wide Island chimney hood
- Box slimline brand design
- Touch control
- Electronic controls
- Light Colour: warm white

PERFORMANCE/TECHNICAL INFORMATION

-

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Twin channel high performance fan motor
- In recirculation operation chimless use possible
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 460 m³/h
 - Intensive 870 m³/h
- Power rating: 172 W
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 54 dB (A) re 1pW
- Noise max. Normal Level: 54 dB*

Light Intensity: 888 lux
Colour Temperature: 3500 K
Electrical cable length 1.3 m
Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
Dimensions exhaust air (HxWxD): 744-924 x 900 x 600 mm
Dimensions recirculating (HxWxD): 744-1044 x 900 x 600 mm
Energy Efficiency Class: A+*
Blower Efficiency Class: A*
Lighting Efficiency Class: A*
Grease Filtering Efficiency Class: B*
Average Energy Consumption: 32.5 kWh/year*

OPTIONAL ACCESSORIES

-

Recirculating kit Z5106X5, Z5102X1, Z5170X1