

**Produktblad vedrørende KOMMISSIONENS DELEGEREDE FORORDNING (EU) nr. 65/2014 af 1. oktober 2013 og KOMMISSIONENS DELEGEREDE FORORDNING (EU) nr. 66/2014 af 14 januar 2014**

---

|                                                                                             |               |
|---------------------------------------------------------------------------------------------|---------------|
| Leverandørens navn eller varemærke                                                          | SMEG S.P.A.   |
| Produktkod                                                                                  | KSEG90XE-2    |
| Annual Efficiency Consumption (AEC <sub>hood</sub> )                                        | 56.1 KWh/year |
| Energy efficiency class (EEC)                                                               | A             |
| Fluid Dynamic Efficiency (FDE)                                                              | 29.5          |
| Fluid Dynamic Efficiency class (FDEC)                                                       | A             |
| Lighting Efficiency (LE)                                                                    | 95 lux/W      |
| Lighting Efficiency Class (LEC)                                                             | A             |
| Grease Filtering Efficiency (GFE)                                                           | 55.1 %        |
| Grease Filtering Efficiency Class (GFEC)                                                    | E             |
| Air flow at minimum speed (Q <sub>min</sub> )                                               | 290 m³/h      |
| Air flow at maximum speed (Q <sub>max</sub> )                                               | 630 m³/h      |
| Air flow at boost speed (Q <sub>boost</sub> )                                               | 800 m³/h      |
| Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPE <sub>min</sub> ) | 50 dB(A)      |
| Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE <sub>max</sub> )  | 68 dB(A)      |
| Airbourne acoustical A-weighted sound power emission at boost speed (SPE <sub>boost</sub> ) | 71 dB(A)      |
| Power Consumption in Off mode (P <sub>o</sub> )                                             | 0.49 W        |
| Time increase factor (F)                                                                    | 0.9           |
| Energy Efficiency Index (EEI)                                                               | 52            |
| Measured air flow rate at best efficiency point (Q <sub>bep</sub> )                         | 372 m³/h      |
| Measured air pressure at best efficiency point (Q <sub>bep</sub> )                          | 474 Pa        |
| Measured electric power input at best efficiency point (W <sub>bep</sub> )                  | 166 W         |
| Normal Power of the light system (W <sub>l</sub> )                                          | 2 W           |
| Average illumination of the light on the cooking surface (E <sub>middle</sub> )             | 210 lux       |
| Sound power level at highest setting (L <sub>wa</sub> )                                     | 68 dB(A)      |

27. marts 2018