

iQ700

Chimney hood

LC91KB672B Black

Angled brand design

A



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 800 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 48 dB the hood is extremely quiet when being used.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-920/582-1030
 Height of product, without chimney (mm) : 387
 Minimum distance above an electric hob : 400
 Minimum distance above a gas hob : 500
 Net weight (kg) : 36.0
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 580
 Boost position output recirculating (m³/h) : 450
 Maximum output recirculating air (m³/h) : 380
 Boost position air extraction (m³/h) : 800
 Number of lights (Stck) : 3
 Noise level (dB(A) re 1 pW) : 62
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 Connection rating (W) : 269
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation type : Wall-mounted



Optional accessories

LZ53450 Recirculating kit

iQ700
Chimney hood
LC91KB672B Black
Angled brand design

Features	
<p>Design</p> <ul style="list-style-type: none">• 90 cm wide• Black• White electronic display• Electronic control via Touch control• Light colour: warm white• For wall mounted installation• Designed for suspended or flush ceiling installation <p>Key features</p> <ul style="list-style-type: none">• Touch control for extractor speeds and light• Boost function• 3 x LED lights• softLight with dimmer function• 1 x metal grease filter cassette• Grease filter saturation indicator• Glass filter cover, Steel filter cover• Rim ventilation	<p>Performance/technical information</p> <ul style="list-style-type: none">• Suitable for ducted and re-circulating operation• For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed• Extraction rate according to EN 61591 ø 15 cm: max. Normal use 580 m³/h Intensive 800 m³/h• Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 62 dB(A) re 1 pW (48 dB(A) re 20 µPa sound pressure) Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)• Additional noise reduction insulation• 3 power levels and 2 intensive settings• Power rating: 269 W• Automatic intensive revert• 10 minutes• Noise max. Normal Level: 62 dB*• Extractor hose 120 mm• Dimensions (WxD): 900 x 426 mm• Dimensions exhaust air (HxWxD): 865-1153 x 900 x 426 mm• Dimensions recirculating with cleanAir module (HxWxD): 1008-1338 x 900 x 426 mm• Diameter pipe Ø 150 mm (Ø 120 mm enclosed)• Light Intensity: 806 lux• Colour Temperature: 3500 K• Average Energy Consumption: 39 kWh/year*• Energy Efficiency Class: A*• Blower Efficiency Class: A*• Lighting Efficiency Class: A*• Grease Filtering Efficiency Class: B* <p><i>* In accordance with the EU-Regulation No 65/2014</i></p>

iQ700

Chimney hood

LC91KB672B Black

Angled brand design

Dimensioned drawings

