

iQ300
iQ 300
Chimney hood
LC97BE532B stainless steel

A+



LED light



iQdrive

Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 730 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ At 41 dB the hood is extremely quiet when being used.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.

Features

Technical Data

Color chimney : Stainless steel
Typology : Chimney
Approval certificates : CE, VDE
Length of electrical supply cord (cm) : 130
Height of the chimney (mm) : 582-894/582-1004
Height of product, without chimney (mm) : 60
Minimum distance above an electric hob : 550
Minimum distance above a gas hob : 650
Net weight (kg) : 19.0
Type of control : Electronic
Number of speed settings : 3
Maximum output air extraction (m³/h) : 460
Boost position output recirculating (m³/h) : 430
Maximum output recirculating air (m³/h) : 350
Boost position air extraction (m³/h) : 730
Number of lights (Stck) : 3
Noise level (dB(A) re 1 pW) : 55
Diameter of air outlet (mm) : 120 / 150
Grease filter material : Washable aluminium
Connection rating (W) : 139
Current (A) : 10
Voltage (V) : 220-240
Frequency (Hz) : 60; 50
Plug type : GB plug
Installation type : Wall-mounted



4 242003 651346

Optional accessories

LZ53450	Recirculating kit
LZ50961	Backboard 90 x 72 cm

iQ300

iQ 300

Chimney hood

LC97BE532B stainless steel

Features

Design

- 90 cm wide
- Day/night glass and metal fascia
- Soft touch button control for extractor speeds and light
- Height adjustable chimney sections
- For wall mounted installation

Key features

- Electronic control
- 3 x LED lights
- 3 x metal grease filter cassettes - dishwasher safe
- Steel filter cover
- Additional noise reduction insulation
- Soft touch button control with illuminated buttons

Performance/technical information

- Suitable for ducted and re-circulating operation
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 460 m³/h
Intensive 730 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at
maximum normal setting: extraction rate: 55 dB (A) re 1pW (41 dB
(A) re 20 µPa sound pressure)
- 3 x power levels plus intensive setting
- Automatic intensive revert
- Adjustable automatic after running

Optional accessories

- Re-circulating kit - LZ52450

LC97BE532B stainless steel

min. 60

245 335

Socket

Exhaust air outlet

min. 500

300

min. 450

min. 550 electric recommendation 650

min. 650 gas*

* from upper edge of pan support

Measurements in mm

