

iQ700
Chimney hood
LC97BF532B stainless steel
Box slimline design



Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 730 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 41 dB the hood is extremely quiet when being used.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-908/582-1018
 Height of product, without chimney (mm) : 46
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 23.0
 Type of control : Electronic
 Number of speed settings : 3
 Maximum output air extraction (m³/h) : 460
 Boost position output recirculating (m³/h) : 430
 Maximum output recirculating air (m³/h) : 350
 Boost position air extraction (m³/h) : 730
 Number of lights (Stck) : 3
 Noise level (dB(A) re 1 pW) : 55
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable aluminium
 Connection rating (W) : 139
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation type : Wall-mounted



Optional accessories

- | | |
|---------|-------------------|
| LZ53450 | Recirculating kit |
| LZ50960 | Backboard |

iQ700

Chimney hood

LC97BF532B stainless steel

Box slimline design

Features

Design

- 90 cm wide
- stainless steel
- Electronic control via Soft touch button control
- Light colour: warm white
- For wall mounted installation

Key features

- Soft touch button control for extractor speeds and light
- 3 x LED lights
- 3 x metal grease filter cassettes - dishwasher safe
- Steel filter cover
- Inner frame

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 460 m³/h
Intensive 730 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 55 dB(A) re 1 pW (41 dB(A) re 20 μ Pa sound pressure)
Intensive: 65 dB(A) re 1 pW (51 dB(A) re 20 μ Pa sound pressure)
- Additional noise reduction insulation
- 3 x power levels plus intensive setting
- Power rating: 139 W
- Automatic intensive revert
- Noise max. Normal Level: 55 dB*
- Extractor hose 120 mm
- Dimensions (WxD): 900 x 500 mm
- Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm
- Dimensions recirculating with cleanAir module (HxWxD): 809-1139 x 900 x 500 mm
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- Light Intensity: 897 lux
- Colour Temperature: 3500 K
- Average Energy Consumption: 32.5 kWh/year*
- Energy Efficiency Class: A+*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*

* In accordance with the EU-Regulation No 65/2014