

iQ700

Chimney hood

LC98BA572B stainless steel

Box slimline design


A⁺

Perfect for smaller spaces the wall-mounted chimney hood features a high extraction rate.

- ✓ The 860 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 41 dB the hood is extremely quiet when being used.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-908/582-1018
 Height of product, without chimney (mm) : 46
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 23.0
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 460
 Boost position output recirculating (m³/h) : 440
 Maximum output recirculating air (m³/h) : 350
 Boost position air extraction (m³/h) : 860
 Number of lights (Stck) : 3
 Noise level (dB(A) re 1 pW) : 55
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable stainless steel
 Connection rating (W) : 169
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation type : Wall-mounted



4 242003 675366

Optional accessories

LZ53450	Recirculating kit
LZ50961	Backboard 90 x 72 cm

iQ700
Chimney hood
LC98BA572B stainless steel
Box slimline design

Features	
<p>Design</p> <ul style="list-style-type: none"> • 90 cm wide • stainless steel • White electronic display • Electronic control via Touch control • Light colour: warm white • For wall mounted installation • Designed for suspended or flush ceiling installation <p>Key features</p> <ul style="list-style-type: none"> • Touch control for extractor speeds and light • Boost function • 3 x LED lights • softLight with dimmer function • 3 x metal grease filter cassettes - dishwasher safe • Grease filter saturation indicator • Steel filter cover • Inner frame 	<p>Performance/technical information</p> <ul style="list-style-type: none"> • Suitable for ducted and re-circulating operation • For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed • Extraction rate according to EN 61591 ø 15 cm: max. Normal use 460 m³/h Intensive 860 m³/h • Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 55 dB(A) re 1 pW (41 dB(A) re 20 µPa sound pressure) Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure) • Additional noise reduction insulation • 3 power levels and 2 intensive settings • Power rating: 169 W • Automatic intensive revert • 10 minutes • Noise max. Normal Level: 55 dB* • Extractor hose 120 mm • Dimensions (WxD): 900 x 500 mm • Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm • Dimensions recirculating with cleanAir module (HxWxD): 809-1139 x 900 x 500 mm • Diameter pipe Ø 150 mm (Ø 120 mm enclosed) • Light Intensity: 897 lux • Colour Temperature: 3500 K • Average Energy Consumption: 37.2 kWh/year* • Energy Efficiency Class: A+* • Blower Efficiency Class: A* • Lighting Efficiency Class: A* • Grease Filtering Efficiency Class: C* <p><i>* In accordance with the EU-Regulation No 65/2014</i></p>