

iQ700

Island chimney hood

LF91BA582B stainless steel

Box slimline design



A

The ceiling-mounted island chimney hood is perfect for all kitchen islands.

- ✓ The 710 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ When required the intensive setting temporarily increases the extraction rate, with automatic revert after 6 min.
- ✓ At 49 dB the hood is extremely quiet when being used.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of the chimney (mm) : 698-878/698-998
 Height of product, without chimney (mm) : 46
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 33.0
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 570
 Boost position output recirculating (m³/h) : 500
 Maximum output recirculating air (m³/h) : 430
 Boost position air extraction (m³/h) : 710
 Number of lights (Stck) : 4
 Noise level (dB(A) re 1 pW) : 63
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable stainless steel
 Connection rating (W) : 272
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : GB plug
 Installation type : Island



4 242003 675373

iQ700
Island chimney hood
LF91BA582B stainless steel
Box slimline design

Features	
<p>Design</p> <ul style="list-style-type: none">• 90 cm wide• stainless steel• White electronic display• Electronic control via Touch control• Light colour: warm white• For ceiling mounted installation• Designed for suspended or flush ceiling installation <p>Key features</p> <ul style="list-style-type: none">• Touch control for extractor speeds and light• climateControl-Sensor• Boost function• 4 x LED lights• 3 x metal grease filter cassettes - dishwasher safe• Grease filter saturation indicator• Steel filter cover, Steel filter cover• Rim ventilation• Inner frame	<p>Performance/technical information</p> <ul style="list-style-type: none">• Suitable for ducted and re-circulating operation• For recirculated extraction CleanAir recirculating kit (accessory) needed• Extraction rate according to EN 61591 ø 15 cm: max. Normal use 570 m³/h Intensive 710 m³/h• Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 63 dB(A) re 1 pW (49 dB(A) re 20 µPa sound pressure) Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)• Additional noise reduction insulation• 3 power levels and 2 intensive settings• Power rating: 272 W• Automatic intensive revert• 10 minutes• Noise max. Normal Level: 63 dB*• Extractor hose 150 mm• Dimensions (WxD): 900 x 600 mm• Dimensions exhaust air (HxWxD): 744-924 x 900 x 600 mm• Dimensions recirculating with cleanAir module (HxWxD): 812-1044 x 900 x 600 mm• Diameter pipe Ø 150 mm (Ø 120 mm enclosed)• Light Intensity: 888 lux• Colour Temperature: 3500 K• Average Energy Consumption: 39.6 kWh/year*• Energy Efficiency Class: A*• Blower Efficiency Class: A*• Lighting Efficiency Class: A*• Grease Filtering Efficiency Class: A* <p><i>* In accordance with the EU-Regulation No 65/2014</i></p>

iQ700

Island chimney hood

LF91BA582B stainless steel

Box slimline design

Dimensioned drawings

